

Specification Sheet - Floordor / FTP

What Size? ANY SIZE!

Floordor access hatches to be supplied by M & M Access Ltd
5 Quarry Park Close, Moulton Park Industrial Estate
Northampton NN3 6QB
Tel: 01604 644944 Fax: 01604 644899



Floordor / FTP flush tread plate lid **single leaf / double leaf / multi leaf** floor access hatch
(Delete as applicable) to have a

Clear opening size of ----- x ----- hinged on the ----- side

To have a load bearing of (FACTA Class Ref) -----

Non fire rated / 1 hour fire rated / 2 hour fire rated / 3 hour fire rated
(Delete as applicable)

Standard Specification

Manufactured from aluminium
A15 Pedestrian loading
Gas spring assisted opening with safety hold open stay.
Stainless steel Cab lock to be opened from inside and key operated from the outside.
Supplied mill finished as standard.

Options

Stainless Steel Construction	Electromagnetic Lock Operated
Polyester Powder Coated	Electrical Actuator Operated
Locking Box	Pneumatic Cylinder Operated
Safety Grill	
Ladder Extension	
Drainage Connection	

Floordor access hatches are a bespoke product, please contact M & M Access Ltd for further assistance

**5 Quarry Park Close
Moulton Park Industrial Estate
Northampton
NN3 6QB**

Tel: 01604 644944 Fax: 01604 644899

Email: sales@m-maccess.co.uk

Web: www.m-maccess.co.uk / www.access-panels.com