

Specification Sheet – Roofdor / G

What Size? ANY SIZE!

Roofdor / G access hatches to be supplied by M & M Access Ltd
5 Quarry Park Close, Moulton Park Industrial Estate
Northampton NN3 6QB
Tel: 01604 644944 Fax: 01604 644899



Roofdor / G – Glazed Non Fire Rated Roof Access Hatch to be **single leaf / double leaf / multi leaf** roof access hatch (Delete as applicable) to have a

Clear opening size of ----- x ----- hinged on the ----- side

Standard Specification

Non Fire Rated – 0.78 U-Value

Manufactured from aluminium

Pilkington Insulight Therm comprising 6mm optifloat clear T annealed, 16mm cavity, 6.4mm

Pilkington optilam K glass laminated

Gas spring assisted opening with safety hold open stay.

Stainless Steel Cab Lock – Internal Opening only

200mm Upstand

Supplied mill finished as standard.

Options

Stainless Steel Construction

Polyester Powder Coated

Safety Grill

Ladder Extension

Walk On Glass

Retractable Hand Hold

Encased Upstand

0.43 U-Value

Electric Actuator Operated

L2 Locking – Internal Hasp & Staple

L3 Locking – External Tee Key

L4 Locking – External Non Locking Handle

L5 Locking – External Locking Handle

L6 Locking – Internal Thumb Turn

L7 Locking – Internal Key & External Key Opening

Increased / Decreased Upstand

Roofdor / G access hatches are a bespoke product, please contact M & M Access Ltd for further assistance

**5 Quarry Park Close
Moulton Park Industrial Estate
Northampton
NN3 6QB**

Tel: 01604 644944 Fax: 01604 644899

Email: sales@m-maccess.co.uk

Web: www.m-maccess.co.uk / www.access-panels.com