

Specification Sheet – Roofdor / S

What Size? ANY SIZE!

Roofdor / S access hatches to be supplied by M & M Access Ltd
5 Quarry Park Close, Moulton Park Industrial Estate
Northampton NN3 6QB
Tel: 01604 644944 Fax: 01604 644899



Roofdor / S – Standard Roof Access Hatch to be **single leaf / double leaf / multi leaf** roof access hatch (Delete as applicable) to have a

Clear opening size of ----- x ----- hinged on the ----- side

Non fire rated / 1 hour fire rated / 2 hour fire rated / 3 hour fire rated
(Delete as applicable)

Standard Specification

Manufactured from aluminium
Gas spring assisted opening with safety hold open stay.
Stainless Steel Cab Lock – Internal Opening only
200mm Upstand
Supplied mill finished as standard.

Options

Stainless Steel Construction
Polyester Powder Coated
Safety Grill
Ladder Extension
Retractable Hand Hold
Encased Upstand
0.43 U-Value
Electric Actuator Operated
L2 Locking – Internal Hasp & Staple
L3 Locking – External Tee Key
L4 Locking – External Non Locking Handle
L5 Locking – External Locking Handle
L6 Locking – Internal Thumb Turn
L7 Locking – Internal Key & External Key Opening
Increased / Decreased Upstand

Roofdor access hatches are a bespoke product, please contact M & M Access Ltd for further assistance

**5 Quarry Park Close
Moulton Park Industrial Estate
Northampton
NN3 6QB**

Tel: 01604 644944 Fax: 01604 644899

Email: sales@m-maccess.co.uk

Web: www.m-maccess.co.uk / www.access-panels.com