



Acousticdor 31dB - Metal faced door within a 57mm deep frame

Fire rated – Acoustic performance 31DB – Smoke Controlled



A Beaded frame design is also available for plastered concealed frame finish



Application

Access Panels are designed to conceal and secure areas in walls and ceilings where access is required to electrical, water and maintenance services, concealed behind or above them. It is designed to be fitted within timber stud/joists, concrete blockwork or metal track systems.

There are two frame surround types;

Picture frame surround to give a neat finish around your pre-cut hole opening.

Beaded frame surround to accept a plaster skim to conceal the frame into your plastered wall.

Description

This access panel has a metal faced door and is supplied with a picture frame. The panel has a continuous piano hinge system which is welded to the door tray and then the door is bolted to the panel frame. The panel is fitted with a **3 point locking system** as standard. The door has an infill of rockwool insulation and soundbloc plasterboard fitted to the rear.

Materials and finishes

M & M access panels are manufactured from 1.2mm thick Zinc plated mild steel (BS EN 10025) for maximum rigidity. Stainless steel finishes are also available.

The Access panels are painted in a polyester powder coating (BS EN 12206-1:2004) – White - RAL 9010 textured, as standard. This paint texture blends well with your plastered painted walls and can be overpainted with ease. Other colours are available to match your finished area.

Sizing

M & M reference panel size sizing from the inside frame measurement – i.e. 600x600

	Panel Size	Structural opening	Clear opening with door open
Example	600x600	610x610	574x548
Formula	Height	+ 10mm	- 24mm
	Width	+ 10mm	- 52mm

Note: Single doors available up to 900mm width then manufactured into double door units.

Rating

This panel construction has been tested to and complies with BS EN ISO 10140-2 for Acoustic performance, giving a 31DB rating. This panel construction also complies with BS EN 1634-1:2014 and BS EN 1363-1:1999 for fire integrity. Smoke control tested and complies with BS EN 1634-3:2004.

Other lock types available

5mm bit insert into the 3 point locking system
IP65 tamperproof insert into the 3 point locking system
Other metal locking options can be considered

Installation

M & M supply installation instructions in the form of labels on the rear of the doors. The label will have the relevant certification standard that it complies to clearly marked.

As part of our quality system you will also find on the label, the identity mark of the quality inspector, who has done the final checks on your product.

