


## Claddor – Plasterboard faced door within a 50mm deep frame

Non – fire rated



### Application

Access Panels are designed to conceal and secure areas in walls and ceilings where access is required to electrical, water and maintenance services, concealed behind or above them. It is designed to be fitted within timber stud/joists, concrete blockwork or metal track systems.

There are two frame surround types;

**Picture frame** surround to give a neat finish around your pre-cut hole opening.

**Beaded frame** surround to accept a plaster skim to conceal the frame into your plastered wall.

### Description

This access panel has a plaster faced door and is supplied with a beaded frame for plaster skim on site to fully conceal the access panel. The panel has a mini piano hinge system welded to the door and bolted to the frame when assembled. The panel is fitted with **3 point locking** as standard, but other locking options are available.

### Materials and finishes

M & M access panels are manufactured from 1.2mm thick Zinc plated mild steel (BS EN 10025) for maximum rigidity. Stainless steel finishes are also available. The Access panels are painted in a polyester powder coating (BS EN 12206-1:2004) – White - RAL 9010 textured, as standard. This paint texture blends well with your plastered walls and can be overpainted with ease. Other colours are available to match your finished area.

### Sizing

M & M reference panel size sizing from the inside frame measurement – i.e. 600x600

|                | Panel Size | Structural opening | Clear opening with door open |
|----------------|------------|--------------------|------------------------------|
| <b>Example</b> | 600x600    | 607x607            | 574x561                      |
| <b>Formula</b> | Height     | + 7mm              | - 24mm                       |
|                | Width      | + 7mm              | - 39mm                       |

Note: Single doors available up to 900mm width then manufactured into double door units.

### Other lock types available

5mm bit insert into 3 point locking  
IP65 tamperproof insert into 3 point locking

### Installation

M & M supply installation instructions in the form of labels on the rear of the doors. The label will have the relevant certification standard that it complies to clearly marked. Any beaded areas for plaster skim must have scrim tape applied to the area before plastering. As part of our quality system you will also find on the label, the identity mark of the quality inspector, who has done the final checks on your product.