


Circledor PB – Plasterboard faced door within a 50mm deep frame

Non – fire rated



Application

Access Panels are designed to conceal and secure areas in walls and ceilings where access is required to electrical, water and maintenance services, concealed behind or above them .

Beaded frame surround to accept a plaster skim to conceal the frame into your plastered wall.

Description

This access panel has a plasterboard faced door and a beaded frame to accept a plaster skim. The panel has a simple hinge system for ease and speed of assembly on site with pin location in the frame and a bayonet fitting in the door. The door is also fitted with safety wires as standard to remove the door safely away from the frame.

Materials and finishes

M & M access panels are manufactured from 1.2mm thick Zinc plated mild steel (BS EN 10025) for maximum rigidity. Stainless steel finishes are also available.

The Access panels are painted in a polyester powder coating (BS EN 12206-1:2004) – White - RAL 9010 textured, as standard. This paint texture blends well with your plastered painted walls and can be overpainted with ease. Other colours are available to match your finished area.

Sizing

M & M reference panel size sizing from the inside frame measurement – i.e. 600x600

	Panel Size	Structural opening	Clear opening with door open
Example	600 diameter	607 diameter	600 diameter
Formula		+ 7mm	-
		+ 7mm	-

Installation

Fixing points are pre-punched in the frames for fixing. The circular hole will need supports to the ceiling to fix the access panel to. Scrim tape must be used before plastering to avoid cracking.